

SAFETY DATA SHEET

Issue Date 24-MAY-2015 Revision Date 24-MAY-2015 Version 2

1. IDENTIFICATION

Product identifier

Product Name PLASTIC ROOF CEMENT

Other means of identification

Product Code PR300 Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Sealant.

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address HENRY COMPANY

999 N. Sepulveda Blvd., Suite 800 El Segundo, CA 90245-2716 Company Contact: Technical Services

Telephone Number: 800-486-1278

Web Site: www.henry.com www.ca.henry.com

Emergency telephone number

Emergency Telephone CHEMTREC: 800-424-9300

CHEMTREC: 703-527-3887 CANUTEC: 613-966-6666

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Not classified
Acute toxicity - Dermal	Not classified
Acute toxicity - Inhalation (Gases)	Not classified
Acute toxicity - Inhalation (Vapors)	Not classified
Acute toxicity - Inhalation (Dusts/Mists)	Not classified
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Respiratory sensitization	Not classified
Skin sensitization	Not classified
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
Specific target organ toxicity (single exposure)	Not classified
Specific target organ toxicity (repeated exposure)	Not classified
Aspiration toxicity	Not classified
Flammable liquids	Category 3

Label elements

Emergency Overview

Warning

Hazard statements

Causes skin irritation

Causes serious eye irritation

May cause respiratory irritation. May cause drowsiness or dizziness

Flammable liquid and vapor



Appearance paste

Physical state liquid

Odor Petroleum distillates

Precautionary Statements - Prevention

Wear protective gloves/protective clothing/eye protection/face protection Keep away from heat/sparks/open flames/hot surfaces. - No smoking Wash face, hands and any exposed skin thoroughly after handling

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water If skin irritation occurs: Get medical advice/attention

IF INHALED: Call a POISON CENTER or doctor if you feel unwell In case of fire: Use Water spray, fog or regular foam for extinction

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

Harmful to aquatic life with long lasting effects

Unknown acute toxicity

29.97% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Chemical Name	CAS No.	Weight-%	Trade Secret
Petroleum Asphalt	8052-42-4	30-50	*
Water	7732-18-5	20-30	
Stoddard solvent	8052-41-3	10-20	*
Clays	NA-Mixture	1-5	*
QUARTZ	14808-60-7	<0.1	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

Eye contact Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids.

Consult a physician.

Skin contact Wash skin with soap and water.

Inhalation Remove to fresh air.

Ingestion Clean mouth with water and drink afterwards plenty of water.

Most important symptoms and effects, both acute and delayed

Symptoms Drowsiness.

Indication of any immediate medical attention and special treatment needed

Note to physiciansTreat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

No information available.

Explosion data

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas.

Environmental precautions

Environmental precautions See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat,

sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static

electricity).

Incompatible materials Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines This product, as supplied, does not contain any hazardous materials with occupational

exposure limits established by the region specific regulatory bodies.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Petroleum Asphalt	TWA: 0.5 mg/m³ benzene soluble	-	Ceiling: 5 mg/m ³ fume 15 min
8052-42-4	aerosol fume, inhalable fraction		
Stoddard solvent	TWA: 100 ppm	TWA: 500 ppm	IDLH: 20000 mg/m ³
8052-41-3		TWA: 2900 mg/m ³	Ceiling: 1800 mg/m ³ 15 min
		(vacated) TWA: 100 ppm	TWA: 350 mg/m ³
		(vacated) TWA: 525 mg/m ³	
QUARTZ	TWA: 0.025 mg/m ³ respirable	(vacated) TWA: 0.1 mg/m ³	IDLH: 50 mg/m ³ respirable dust
14808-60-7	fraction	respirable dust	TWA: 0.05 mg/m ³ respirable dust
		: (30)/(%SiO2 + 2) mg/m ³ TWA	
		total dust	
		: (250)/(%SiO2 + 5) mppcf TWA	
		respirable fraction	
		: (10)/(%SiO2 + 2) mg/m³ TWA	
		respirable fraction	

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective gloves and protective clothing.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical stateliquidAppearancepasteOdorPetroleum distillatesColorblackOdor thresholdNo information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH No information availableMelting point / freezing point No information available

Boiling point / boiling range >= 150 °C Flash point 40 °C

Evaporation rate No information available

Flammability (solid, gas) No information available

Flammability Limit in Air

Upper flammability limit: 9% Lower flammability limit: 1%

Vapor pressureNo information availableVapor densityNo information available

Relative density 0.9 - 1.3

Water solubility
Solubility in other solvents
Partition coefficient
Autoignition temperature
Decomposition temperature
No information available
No information available
No information available

Kinematic viscosity >100 mm2/s @ 40 °C

Dynamic viscosityNo information availableExplosive propertiesNo information availableOxidizing propertiesNo information available

Other Information

Softening point
Molecular weight
VOC Content (%)
Density
No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Extremes of temperature and direct sunlight.

Incompatible materials

Strong oxidizing agents.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information No data available

Inhalation May cause irritation of respiratory tract. May cause drowsiness or dizziness.

Eye contact Irritating to eyes.

Skin contact Irritating to skin.

Ingestion No data available.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Petroleum Asphalt	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-
8052-42-4			
QUARTZ	= 500 mg/kg (Rat)	-	-
14808-60-7			

Information on toxicological effects

Symptoms Vapors may cause drowsiness and dizziness.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

SensitizationNo information available.Germ cell mutagenicityNo information available.CarcinogenicityNo information available.

Chemical Name	ACGIH	IARC	NTP	OSHA
Petroleum Asphalt	-	Group 2B	=	X
8052-42-4				
QUARTZ	A2	Group 1	Known	X
14808-60-7		·		

Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
Aspiration hazard
No information available.
No information available.
No information available.

Numerical measures of toxicity - Product Information

 ATEmix (oral)
 5,602.00

 ATEmix (dermal)
 5,602.00

 ATEmix (inhalation-gas)
 99,999.00

 ATEmix (inhalation-dust/mist)
 14.01

 ATEmix (inhalation-vapor)
 99,999.00

12. ECOLOGICAL INFORMATION

Ecotoxicity

49.4 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Persistence and degradability

Not readily biodegradable.

Bioaccumulation

No information available.

Chemical Name	Partition coefficient
Petroleum Asphalt	>6
8052-42-4	

Other adverse effects No information available

Ozone Not applicable

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

14. TRANSPORT INFORMATION

DOTNot regulated (If shipped in NON BULK packaging by ground transport)

TDG Not regulated

IATA

UN/ID no. UN1999
Proper shipping name Tars, Liquid

Hazard Class 3
Packing Group III

IMDG

UN1999 Proper shipping name UN1999 Tars, Liquid

Hazard Class 3
Packing Group III

Description May be transported as non-hazardous in accordance with IMDG 2.3.2.5

15. REGULATORY INFORMATION

All components used in this product are on the TSCA Inventory and the Canadian DSL.

International Inventories

TSCA Complies Complies DSL/NDSL **EINECS/ELINCS** Complies **ENCS** Does not comply **IECSC** Complies **KECL** Complies **PICCS** Complies **AICS** Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute health hazardYesChronic Health HazardNoFire hazardNoSudden release of pressure hazardNo

Reactive Hazard

No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product contains chemicals known to the state of California to cause birth defects or other reproductive harm

U.S. State Right-to-Know Regulations

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 2 Instability 0 Physical and Chemical

Properties -

Health hazards 2 Flammability 2 Physical hazards 0 Personal protection X

 Issue Date
 24-MAY-2015

 Revision Date
 24-MAY-2015

Revision Note

No information available

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet