



Revision Number: 001.3

Issue date: 10/10/2014

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:	Loctite Polyseamseal Caulk + All Purpose	IDH number:	1700176
Product type:	Sealant	Region:	United States
Restriction of Use:	None identified	Contact information:	Telephone: +1 (800) 624-7767
Company address:	Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067		MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

NOT CLASSIFIED. READ ENTIRE SAFETY DATA SHEET.

HAZARD CLASS	HAZARD CATEGORY
None	None

PICTOGRAM(S)

None

Precautionary Statements

Prevention:	Not prescribed
Response:	Not prescribed
Storage:	Not prescribed
Disposal:	Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
None	None	None

* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If symptoms persist, seek medical advice.
Skin contact:	Wash affected area immediately with soap and water. If symptoms develop and persist, get medical attention.
Eye contact:	If irritation develops, flush eyes immediately with large amounts of water. If irritation persists, seek medical attention or advice.

Ingestion: Rinse out mouth. Do not drink. Never give anything by mouth to an unconscious person. If adverse health effects develop seek medical attention.

Symptoms: See Section 11.

Notes to physician: Treat symptomatically and supportively.

5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Water may be unsuitable as an extinguishing media, but may be helpful in keeping adjacent containers cool.

Unusual fire or explosion hazards: Closed containers may explode when exposed to extreme heat.

Hazardous combustion products: Oxides of nitrogen. Oxides of carbon.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not let product enter drains.

Clean-up methods: Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Absorb spill with inert material. Shovel material into appropriate container for disposal. Wear appropriate protective equipment and clothing during clean-up.

7. HANDLING AND STORAGE

Handling: Avoid contact with eyes. Avoid prolonged or repeated skin contact with this material. Keep out of the reach of children.

Storage: Keep from freezing.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
None	None	None	None	None

Engineering controls: Use local exhaust ventilation.

Respiratory protection: No personal respiratory protective equipment normally required.

Eye/face protection: None required in normal use.

Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: pasty

Color: Clear

Odor: Acrylic

Odor threshold: Not available.

pH: 7.7 - 8.6

Vapor pressure: 15 mm hg (20 °C (68°F))

Boiling point/range: 100 °C (212°F)
Melting point/ range: Not available.
Specific gravity: 1.06
Vapor density: Heavier than air, (Air = 1)
Flash point: > 200 °F (> 93.33 °C) Pensky Martens closed cup
Flammable/Explosive limits - lower: Not available.
Flammable/Explosive limits - upper: Not available.
Autoignition temperature: Not available.
Evaporation rate: 0.5 (Butyl acetate = 1)
Solubility in water: Soluble
Partition coefficient (n-octanol/water): Not available.
VOC content: 1 %; < 15 g/l (by weight, calculated using CARB method; g/L less water, less exempts calculated using SCAQMD method)
Viscosity: 250,000 - 350,000 cp
Decomposition temperature: Not available.

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.
Hazardous reactions: Will not occur.
Hazardous decomposition products: Oxides of carbon. Oxides of nitrogen.
Incompatible materials: This product may react with strong oxidizing agents.
Reactivity: Not available.
Conditions to avoid: Keep away from heat, ignition sources and incompatible materials.

11. TOXICOLOGICAL INFORMATION

Product toxicity data: Henkel is not aware of any toxicity data on the specific mixture of chemical components contained in this product.
Relevant routes of exposure: Skin
Potential Health Effects/Symptoms
Inhalation: Inhalation of vapors from uncured sealant may cause respiratory tract irritation.
Skin contact: Prolonged or repeated contact with this product may dry and/or defat the skin.
Eye contact: Contact with uncured product may irritate the eyes.
Ingestion: Ingestion of this product is unlikely. However, ingestion of product may produce gastrointestinal irritation and disturbances.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
None	None	None

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
None	None	None	None

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:	Dispose of according to Federal, State and local governmental regulations.
Hazardous waste number:	It is the responsibility of the user to determine if an item is hazardous as defined in the Resource Conservation and Recovery Act (RCRA) at the time of disposal. Product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability, corrosivity, reactivity and toxicity characteristics of the Toxicity Characteristics Leaching Procedure (TCLP) 40 CFR 261.20-24.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

International Air Transportation (ICAO/IATA)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

Water Transportation (IMO/IMDG)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification:	None above reporting de minimis
CERCLA/SARA Section 302 EHS:	None above reporting de minimis
CERCLA/SARA Section 311/312:	None
CERCLA/SARA Section 313:	None above reporting de minimis
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. This product contains a chemical known in the State of California to cause cancer.

Canada Regulatory Information

CEPA DSL/NDL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.
-----------------------------	---

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format.

Prepared by: Mary Ellen Roddy, Sr. Regulatory Affairs Specialist

Issue date: 10/10/2014

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.