## SAFETY DATA SHEET

8300

### **Section 1. Identification**

Product name : KRYLON® LINE-UP® Striping Paint (Solvent Based)

Highway White

Product code : 8300

Other means of identification

: Not available.

Product type : Aerosol.

Relevant identified uses of the substance or mixture and uses advised against

Paint or paint related material.

**Manufacturer**: Krylon Products Group

101 Prospect Avenue NW Cleveland, OH 44115

Emergency telephone number of the company

: US/Canada: (800) 424-9300

Mexico: CHEMTREC Mexico 800-681-9531. Available 24 hours and 365 days per year

Product Information Telephone Number

: US/Canada: (800) 247-3266 Mexico: Not Available

**Transportation Emergency** 

: US/Canada: (800) 424-9300

**Telephone Number** 

Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

### Section 2. Hazards identification

**OSHA/HCS** status

: This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Classification of the substance or mixture

: AEROSOLS - Category 1

SKIN CORROSION/IRRITATION - Category 2

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A

**CARCINOGENICITY - Category 2** 

TOXIC TO REPRODUCTION - Category 1B

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) -

Category 3

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2

ASPIRATION HAZARD - Category 1

Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 20.7%

(oral), 28.5% (dermal), 20.7% (inhalation)

**GHS label elements** 

8300

Hazard pictograms :







Signal word : Danger

Date of issue/Date of revision : 9/14/2025 Date of previous issue : 7/30/2025 Version : 30.04 1/24

KRYLON® LINE-UP® Striping Paint (Solvent Based)

Highway White

#### Section 2. Hazards identification

#### **Hazard statements**

: Extremely flammable aerosol. Pressurized container: may burst if heated.

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer.

May damage fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure.

#### **Precautionary statements**

#### **Prevention**

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Use only outdoors or in a well-ventilated area. Do not breathe dust or mist. Wash thoroughly after handling. Do not pierce or burn, even after use.

#### Response

: IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

#### **Storage**

: Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 122 \ °F/50 °C. Store in a well-ventilated place. Keep container tightly closed.

#### **Disposal**

Dispose of contents and container in accordance with all local, regional, national and international regulations.

## Supplemental label elements

DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. FOR INDUSTRIAL USE ONLY.

Please refer to the SDS for additional information. Keep out of reach of children. Keep upright in a cool, dry place. Do not discard empty can in trash compactor.

## Hazards not otherwise classified

: DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations.

## Hazards identified when

: No known significant effects or critical hazards.

## Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Other means of identification

8300

: Not available.

**CAS** number/other identifiers

Date of issue/Date of revision : 9/14/2025 Date of previous issue : 7/30/2025 Version : 30.04 2/24

## Section 3. Composition/information on ingredients

Ingredient name	% by weight	Identifiers
Acetone	≥10 - ≤25	67-64-1
Lt. Aliphatic Hydrocarbon Solvent	≥10 - ≤25	64742-89-8
Propane	≥10 - ≤25	74-98-6
Butane	≤10	106-97-8
Toluene	≤10	108-88-3
Titanium Dioxide	≤10	13463-67-7
Xylene, mixed isomers	<1	1330-20-7
Light Aliphatic Hydrocarbon	≤0.3	64742-47-8
Ethylbenzene	≤0.3	100-41-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

#### Section 4. First aid measures

#### **Description of necessary first aid measures**

**Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it

is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open

airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing

before reuse. Clean shoes thoroughly before reuse.

Ingestion : Get medical attention immediately. Call a poison center or physician. Wash out mouth

with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical

attention immediately. Maintain an open airway. Loosen tight clothing such as a collar,

tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or

dizziness.

Skin contact : Causes skin irritation.

**Ingestion**: Can cause central nervous system (CNS) depression. May be fatal if swallowed and

enters airways.

#### Over-exposure signs/symptoms

Date of issue/Date of revision: 9/14/2025Date of previous issue: 7/30/2025Version: 30.043/24

8300 KRYLON® LINE-UP® Striping Paint (Solvent Based) SHW-85-NA-GHS-US

### Section 4. First aid measures

**Eye contact** : Adverse symptoms may include the following:

pain or irritation watering redness

**Inhalation** : Adverse symptoms may include the following:

respiratory tract irritation

coughing

nausea or vomiting

headache

drowsiness/fatigue dizziness/vertigo unconsciousness reduced fetal weight increase in fetal deaths skeletal malformations

**Skin contact**: Adverse symptoms may include the following:

irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

**Ingestion**: Adverse symptoms may include the following:

nausea or vomiting reduced fetal weight increase in fetal deaths skeletal malformations

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments**: No specific treatment.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is

suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water

before removing it, or wear gloves.

#### See toxicological information (Section 11)

## Section 5. Fire-fighting measures

#### **Extinguishing media**

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing** 

media

8300

: None known.

# Specific hazards arising from the chemical

: Extremely flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.

Date of issue/Date of revision : 9/14/2025 Date of previous issue : 7/30/2025 Version : 30.04 4/24

KRYLON® LINE-UP® Striping Paint (Solvent Based) Highway White

## Section 5. Fire-fighting measures

# Hazardous thermal decomposition products

: Decomposition products may include the following materials: carbon dioxide

carbon monoxide metal oxide/oxides

# Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

# Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Remark

: Flammable aerosol.

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

#### **Environmental precautions**

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and materials for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

## Section 7. Handling and storage

#### Precautions for safe handling

**Protective measures** 

Put on appropriate personal protective equipment (see Section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Avoid breathing gas. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from

Date of issue/Date of revision : 9/14/2025 Date of previous issue : 7/30/2025 Version : 30.04 5/24

## Section 7. Handling and storage

#### Advice on general occupational hygiene

heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

## including any incompatibilities

Conditions for safe storage, : Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

#### **Control parameters**

Occupational exposure limits (OSHA United States)

Ingredient name	CAS#	Exposure limits
Acetone	67-64-1	ACGIH TLV (United States, 1/2024) A4. TWA 8 hours: 250 ppm. STEL 15 minutes: 500 ppm. NIOSH REL (United States, 10/2020) TWA 10 hours: 250 ppm. TWA 10 hours: 590 mg/m³. OSHA PEL (United States, 5/2018) TWA 8 hours: 1000 ppm. TWA 8 hours: 2400 mg/m³.
Lt. Aliphatic Hydrocarbon Solvent	64742-89-8	ACGIH TLV (United States, 1/2024) [branched hexane isomers] A3.  TWA 8 hours: 200 ppm.  ACGIH TLV (United States, 1/2024) [hexane] A3. Absorbed through skin.  TWA 8 hours: 100 ppm.  NIOSH REL (United States, 10/2020) [HEXANE ISOMERS]  TWA 10 hours: 100 ppm.  TWA 10 hours: 350 mg/m³.  CEIL 15 minutes: 510 ppm.  CEIL 15 minutes: 1800 mg/m³.
Propane	74-98-6	ACGIH TLV (United States, 1/2024) Oxygen depletion [asphyxiant], Explosive potential.  NIOSH REL (United States, 10/2020)  TWA 10 hours: 1000 ppm.  TWA 10 hours: 1800 mg/m³.  OSHA PEL (United States, 5/2018)  TWA 8 hours: 1000 ppm.  TWA 8 hours: 1800 mg/m³.
Butane	106-97-8	ACGIH TLV (United States, 1/2024) [Butane] Explosive potential. STEL 15 minutes: 1000 ppm. NIOSH REL (United States, 10/2020) TWA 10 hours: 800 ppm. TWA 10 hours: 1900 mg/m³.
Toluene	108-88-3	ACGIH TLV (United States, 1/2024) A4.

Date of issue/Date of revision

: 9/14/2025

Date of previous issue

: 7/30/2025

Version: 30.04

6/24

KRYLON® LINE-UP® Striping Paint (Solvent Based)

Highway White

		Ototoxicant.
		TWA 8 hours: 20 ppm.  OSHA PEL Z2 (United States, 2/2013)  TWA 8 hours: 200 ppm.  CEIL: 300 ppm.  AMP 10 minutes: 500 ppm.  NIOSH REL (United States, 10/2020)  TWA 10 hours: 100 ppm.  TWA 10 hours: 375 mg/m³.  STEL 15 minutes: 150 ppm.  STEL 15 minutes: 560 mg/m³.
Titanium Dioxide	13463-67-7	ACGIH TLV (United States, 1/2024) A3.  TWA 8 hours: 2.5 mg/m³. Form: respirable fraction, finescale particles.  NIOSH REL (United States, 10/2020) NIA.  OSHA PEL (United States, 5/2018)  TWA 8 hours: 15 mg/m³. Form: Total dust.
Xylene, mixed isomers	1330-20-7	ACGIH TLV (United States, 1/2024) [p-xylene and mixtures containing p-xylene] A4. Ototoxicant. TWA 8 hours: 20 ppm. OSHA PEL (United States, 5/2018) [Xylenes] TWA 8 hours: 100 ppm. TWA 8 hours: 435 mg/m³.
Light Aliphatic Hydrocarbon	64742-47-8	ACGIH TLV (United States, 1/2024) [Kerosene] A3. Absorbed through skin. TWA 8 hours: 200 mg/m³ (as total hydrocarbon vapor).
Ethylbenzene	100-41-4	ACGIH TLV (United States, 1/2024) A3. Ototoxicant. TWA 8 hours: 20 ppm. NIOSH REL (United States, 10/2020) TWA 10 hours: 100 ppm. TWA 10 hours: 435 mg/m³. STEL 15 minutes: 125 ppm. STEL 15 minutes: 545 mg/m³. OSHA PEL (United States, 5/2018) TWA 8 hours: 100 ppm. TWA 8 hours: 435 mg/m³.

#### Occupational exposure limits (Canada)

Ingredient name	CAS#	Exposure limits
acetone	67-64-1	CA Saskatchewan Provincial (Canada, 4/2021)  STEL 15 minutes: 750 ppm.  TWA 8 hours: 500 ppm.  CA British Columbia Provincial (Canada, 9/2024)  TWA 8 hours: 250 ppm.  STEL 15 minutes: 500 ppm.  CA Ontario Provincial (Canada, 6/2019)  TWA 8 hours: 250 ppm.  STEL 15 minutes: 500 ppm.  CA Quebec Provincial (Canada, 2/2024)  TWAEV 8 hours: 250 ppm.

Date of issue/Date of revision

8300

: 9/14/2025

Date of previous issue

: 7/30/2025

Version : 30.04

7/24

Section 8. Exposure contro	ois/personai proi	lection
Lt. Aliphatic Hydrocarbon Solvent	64742-89-8	STEV 15 minutes: 500 ppm.  CA Alberta Provincial (Canada, 3/2023)  OEL 8 hours: 1200 mg/m³.  OEL 15 minutes: 1800 mg/m³.  OEL 8 hours: 500 ppm.  OEL 15 minutes: 750 ppm.  CA Saskatchewan Provincial (Canada,
		A/2021) [Hexane] STEL 15 minutes: 1000 ppm. TWA 8 hours: 500 ppm.  CA British Columbia Provincial (Canada, 9/2024) [hexane, all isomers except n-hexane] TWA 8 hours: 200 ppm.  CA British Columbia Provincial (Canada, 9/2024) [hexane] Absorbed through skin.  Notes: No British Columbia exposure limit at this time CA Ontario Provincial (Canada, 6/2019) [Hexane isomers, other than n-hexane] TWA 8 hours: 500 ppm. STEL 15 minutes: 1000 ppm. CA Quebec Provincial (Canada, 2/2024) [Hexane] TWAEV 8 hours: 500 ppm. TWAEV 8 hours: 1760 mg/m³. STEV 15 minutes: 1000 ppm. STEV 15 minutes: 3500 mg/m³. CA Alberta Provincial (Canada, 3/2023) [Dimethylbutane] OEL 8 hours: 1760 mg/m³. OEL 15 minutes: 3500 mg/m³. OEL 8 hours: 500 ppm. CA Alberta Provincial (Canada, 3/2023) [Hexane] OEL 8 hours: 1760 mg/m³. OEL 8 hours: 500 ppm. CA Alberta Provincial (Canada, 3/2023) [Hexane] OEL 8 hours: 500 ppm. OEL 15 minutes: 3500 mg/m³. OEL 15 minutes: 3500 mg/m³.
Normal propane	74-98-6	CA Saskatchewan Provincial (Canada, 4/2021)  STEL 15 minutes: 1250 ppm.  TWA 8 hours: 1000 ppm.  CA British Columbia Provincial (Canada, 9/2024) Oxygen depletion [asphyxiant], Explosive potential.  CA Ontario Provincial (Canada, 6/2019) Oxygen depletion [asphyxiant], Explosive potential.  CA Quebec Provincial (Canada, 2/2024) Oxygen depletion [asphyxiant], Explosive potential.  CA Alberta Provincial (Canada, 3/2023) OEL 8 hours: 1000 ppm.
Butane	106-97-8	CA Saskatchewan Provincial (Canada, 4/2021) [Aliphatic hydrocarbon gases,
Date of issue/Date of revision • 9/14/2025	Date of previous issue	·7/30/2025 Version ·30.04 8/24

Date of issue/Date of revision : 9/14/2025 Date of previous issue : 7/30/2025 Version: 30.04 8/24

8300

Section 8. Exposure controls/pe	ersonal prot	tection
		Alkane [C1-C4]] STEL 15 minutes: 1250 ppm. TWA 8 hours: 1000 ppm. CA Saskatchewan Provincial (Canada, 4/2021) [Butane] STEL 15 minutes: 1250 ppm. TWA 8 hours: 1000 ppm. CA British Columbia Provincial (Canada, 9/2024) [butane, all isomers] Explosive potential. STEL 15 minutes: 1000 ppm. CA Ontario Provincial (Canada, 6/2019) [Butane, All isomers] Explosive potential. STEL 15 minutes: 1000 ppm. CA Quebec Provincial (Canada, 2/2024) TWAEV 8 hours: 800 ppm. TWAEV 8 hours: 1900 mg/m³. CA Alberta Provincial (Canada, 3/2023) OEL 8 hours: 1000 ppm.
toluene	108-88-3	CA Saskatchewan Provincial (Canada, 4/2021) Absorbed through skin.  STEL 15 minutes: 60 ppm.  TWA 8 hours: 50 ppm.  CA British Columbia Provincial (Canada, 9/2024) Repr.  TWA 8 hours: 20 ppm.  CA Ontario Provincial (Canada, 6/2019)  TWA 8 hours: 20 ppm.  CA Quebec Provincial (Canada, 2/2024)  Ototoxicant.  TWAEV 8 hours: 20 ppm.  CA Alberta Provincial (Canada, 3/2023)  Absorbed through skin.  OEL 8 hours: 50 ppm.  OEL 8 hours: 188 mg/m³.
Xylene	1330-20-7	CA Saskatchewan Provincial (Canada, 4/2021) [Xylene]  STEL 15 minutes: 150 ppm. TWA 8 hours: 100 ppm.  CA British Columbia Provincial (Canada, 9/2024) [xylene (o, m & p isomers)]  TWA 8 hours: 100 ppm.  STEL 15 minutes: 150 ppm.  CA Ontario Provincial (Canada, 6/2019)  [Xylene (o-, m-, p-isomers)]  STEL 15 minutes: 150 ppm.  TWA 8 hours: 100 ppm.  CA Quebec Provincial (Canada, 2/2024)  [Xylene]  TWAEV 8 hours: 100 ppm.  TWAEV 8 hours: 434 mg/m³.  STEV 15 minutes: 150 ppm.  STEV 15 minutes: 651 mg/m³.  CA Alberta Provincial (Canada, 3/2023)  [Dimethylbenzene]  OEL 8 hours: 100 ppm.  OEL 15 minutes: 651 mg/m³.
Date of issue/Date of revision : 0/14/2025 Date of	formations in a	• 7/20/2025 Varsian • 20.04 0/24

Date of issue/Date of revision : 9/14/2025 Date of previous issue : 7/30/2025 Version : 30.04 9/24

8300

		OEL 15 minutes: 150 ppm.
Petroleum refining, hydrotreated light distillate	64742-47-8	OEL 8 hours: 434 mg/m³.  CA British Columbia Provincial (Canada,
		9/2024) [kerosene/jet fuels] Absorbed through skin.  TWA 8 hours: 200 mg/m³ (as total hydrocarbon vapour). Notes: Application restricted to conditions in which there are negligible aerosol exposures.  CA Ontario Provincial (Canada, 6/2019)  Absorbed through skin.  TWA 8 hours: 200 mg/m³ (as total hydrocarbon vapour).  CA Quebec Provincial (Canada, 2/2024)  [kerosene] C3. Absorbed through skin.  TWAEV 8 hours: 200 mg/m³.  CA Alberta Provincial (Canada, 3/2023)  [Kerosene/Jet fuels] Absorbed through skin.  OEL 8 hours: 200 mg/m³ (as total hydrocarbon vapour).
Ethylbenzene	100-41-4	CA Saskatchewan Provincial (Canada, 4/2021)  STEL 15 minutes: 125 ppm.  TWA 8 hours: 100 ppm.  CA British Columbia Provincial (Canada, 9/2024) Carc 2B.  TWA 8 hours: 20 ppm.  CA Ontario Provincial (Canada, 6/2019)  TWA 8 hours: 20 ppm.  CA Quebec Provincial (Canada, 2/2024)  C3.  TWAEV 8 hours: 20 ppm.  CA Alberta Provincial (Canada, 3/2023)  OEL 8 hours: 100 ppm.  OEL 8 hours: 434 mg/m³.  OEL 15 minutes: 543 mg/m³.  OEL 15 minutes: 125 ppm.

#### Occupational exposure limits (Mexico)

Ingredient name	CAS#	Exposure limits
Acetone	67-64-1	NOM-010-STPS-2014 (Mexico, 4/2016) A4. TWA 8 hours: 500 ppm. STEL 15 minutes: 750 ppm.
Lt. Aliphatic Hydrocarbon Solvent	64742-89-8	ACGIH TLV (United States, 1/2024) [branched hexane isomers] A3. TWA 8 hours: 200 ppm. ACGIH TLV (United States, 1/2024) [hexane] A3. Absorbed through skin. TWA 8 hours: 100 ppm.
Toluene	108-88-3	NOM-010-STPS-2014 (Mexico, 4/2016) A4. TWA 8 hours: 20 ppm.

**Biological exposure indices (United States)** 

Date of issue/Date of revision: 9/14/2025Date of previous issue: 7/30/2025Version: 30.0410/248300KRYLON® LINE-UP® Striping Paint (Solvent Based)<br/>Highway WhiteSHW-85-NA-GHS-US<br/>Highway White

Ingredient name	Exposure indices
Acetone	ACGIH BEI (United States, 1/2024) BEI: 25 mg/l, acetone [in urine]. Sampling time: end of shift.
Toluene	ACGIH BEI (United States, 1/2024) BEI: 0.03 mg/l, toluene [in urine]. Sampling time: end of shift. BEI: 0.3 mg/g creatinine, o-cresol [in urine]. Sampling time: end of shift. BEI: 0.02 mg/l, toluene [in blood]. Sampling time: prior to last shift of workweek.
Xylene, mixed isomers	ACGIH BEI (United States, 1/2024) [xylenes (technical or commercial grades)] BEI: 0.3 g/g creatinine, methylhippuric acids [in urine]. Sampling time: end of shift.
Ethylbenzene	ACGIH BEI (United States, 1/2024) BEI: 150 mg/g creatinine, sum of mandelic acid and phenylglyoxylic acid [in urine]. Sampling time: end of shift.

#### **Biological exposure indices (Canada)**

No exposure indices known.

#### **Biological exposure indices (Mexico)**

Ingredient name	Exposure indices
Acetone	Official Mexican STANDARD NOM- 047-SSA1-2011, Environmental Health- Biological exposure indices for personnel occupationally exposed to chemical substances. (Mexico, 6/2012) BEI: 50 mg/L [non-specific.The determinant is nonspecific, since it can be found after exposure to other chemicals.], acetone [in urine]. Sampling time: at the end of the work shift.
Toluene	Official Mexican STANDARD NOM- 047-SSA1-2011, Environmental Health- Biological exposure indices for personnel occupationally exposed to chemical substances. (Mexico, 6/2012)  BEI: 0.05 mg/L, toluene [in blood]. Sampling time: sample time not specified.  BEI: 1.6 g/g creatinine [Basal level.The determinant may be present in the biological sample obtained from subjects who have not been occupationally exposed, at a concentration that could affect the interpretation of the results. These background levels are included in the valu; non-specific.The determinant is nonspecific, since it can be found after exposure to other chemicals.], hippuric acid [in urine]. Sampling

Date of issue/Date of revision

: 9/14/2025 Date of previous issue

: 7/30/2025

Version: 30.04

11/24

time: at the end of the work shift.
BEI: 0.5 mg/L [Basal level.The determinant may be present in the biological sample obtained from subjects who have not been occupationally exposed, at a concentration that could affect the interpretation of the results. These background levels are included in the valu], o-cresol [in urine]. Sampling time: at the end of the work shift.

## Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

## **Environmental exposure** controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### **Eye/face protection**

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

# Skin protection Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

#### **Body protection**

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear antistatic protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

#### Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Date of issue/Date of revision : 9/14/2025 Date of previous issue : 7/30/2025 Version : 30.04 12/24

## Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### **Appearance**

Physical state : Liquid.
Color : White.

Odor threshold : Not available.

Not available.

**pH** : 7

Melting point/freezing point : Not available.

Boiling point or initial : Not available.

boiling point and boiling

range

Flash point : Closed cup: -29°C (-20.2°F) [Pensky-Martens Closed Cup]

**Evaporation rate** : 5.6 (butyl acetate = 1) **Flammability** : Flammable aerosol.

Lower and upper explosion limit/flammability limit

: Lower: 0.9% Upper: 12.8%

Vapor pressure : 101.3 kPa (760 mm Hg)

**Relative vapor density** : 1.55 [Air = 1]

Relative density : 0.89

Density : 0.89 g/cm³

Solubility(ies)

Media	Result
cold water	Not soluble

Partition coefficient: n-

octanol/water

: Not applicable.

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Viscosity : Dynamic (room temperature): Not available.

Kinematic (room temperature): Not available.

Kinematic (40°C (104°F)): <20.5 mm<sup>2</sup>/s (<20.5 cSt)

Molecular weight : Not applicable.

**Particle characteristics** 

Median particle size : Not applicable.

Aerosol product

Type of aerosol : Spray
Heat of combustion : 22.918 kJ/g

### Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability**: The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Date of issue/Date of revision : 9/14/2025 Date of previous issue : 7/30/2025 Version : 30.04 13/24

8300 KRYLON® LINE-UP® Striping Paint (Solvent Based)

Highway White

### Section 10. Stability and reactivity

**Conditions to avoid** : Avoid all possible sources of ignition (spark or flame).

Incompatible materials : No specific data.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

## Section 11. Toxicological information

#### Information on toxicological effects

**Acute toxicity** 

Butane

Product/ingredient name Result

Acetone Rat - Oral - LD50

5800 mg/kg

Toxic effects: Behavioral - Altered sleep time (including change in

righting reflex) Behavioral - Tremor

Rat - Inhalation - LC50 Vapor

658000 mg/m³ [4 hours]

Toluene Rat - Oral - LD50

636 mg/kg

Rat - Inhalation - LC50 Vapor

49 g/m³ [4 hours]

Xylene, mixed isomers Rat - Oral - LD50

4300 mg/kg

<u>Toxic effects</u>: Liver - Other changes Kidney, Ureter, and Bladder -

Other changes

Rat - Inhalation - LC50 Gas.

6700 ppm [4 hours]

Toxic effects: Behavioral - Somnolence (general depressed

activity)

Ethylbenzene Rat - Oral - LD50

3500 mg/kg

Toxic effects: Liver - Other changes Kidney, Ureter, and Bladder -

Other changes

Rabbit - Dermal - LD50

>5000 mg/kg

**Conclusion/Summary [Product]**: Not available.

Skin corrosion/irritation

Product/ingredient name Result

Acetone Rabbit - Skin - Mild irritant

<u>Duration of treatment/exposure</u>: 24 hours <u>Amount/concentration applied</u>: 500 mg

Rabbit - Skin - Mild irritant

Amount/concentration applied: 395 mg

Toluene Pig - Skin - Mild irritant

<u>Duration of treatment/exposure</u>: 24 hours <u>Amount/concentration applied</u>: 250 uL

Rabbit - Skin - Mild irritant

Amount/concentration applied: 435 mg

Rabbit - Skin - Moderate irritant

Duration of treatment/exposure: 24 hours

Amount/concentration applied: 20 mg

Date of issue/Date of revision : 9/14/2025 Date of previous issue : 7/30/2025 Version : 30.04 14/24

8300 KRYLON® LINE-UP® Striping Paint (Solvent Based) SHW-85-NA-GHS-US

Rabbit - Skin - Moderate irritant

Amount/concentration applied: 500 mg

Human - Skin - Mild irritant

Duration of treatment/exposure: 72 hours Amount/concentration applied: 300 ug I

Rat - Skin - Mild irritant

Duration of treatment/exposure: 8 hours Amount/concentration applied: 60 uL Rabbit - Skin - Moderate irritant Duration of treatment/exposure: 24 hours Amount/concentration applied: 500 mg

Rabbit - Skin - Moderate irritant Amount/concentration applied: 100 %

Rabbit - Skin - Mild irritant

<u>Duration of treatment/exposure</u>: 24 hours Amount/concentration applied: 15 mg

**Conclusion/Summary [Product]** : Not available.

Serious eye damage/eye irritation

Titanium Dioxide

Ethylbenzene

Xylene, mixed isomers

Product/ingredient name Result

Acetone **Human - Eyes - Mild irritant** 

Amount/concentration applied: 186300 ppm

Rabbit - Eyes - Mild irritant

Amount/concentration applied: 10 uL Rabbit - Eyes - Moderate irritant Duration of treatment/exposure: 24 hours Amount/concentration applied: 20 mg Rabbit - Eyes - Severe irritant Amount/concentration applied: 20 mg

Toluene Rabbit - Eyes - Mild irritant

> **Duration of treatment/exposure**: 0.5 minutes Amount/concentration applied: 100 mg

Rabbit - Eyes - Mild irritant

Amount/concentration applied: 870 ug

Rabbit - Eyes - Severe irritant

Duration of treatment/exposure: 24 hours Amount/concentration applied: 2 mg Rabbit - Eyes - Severe irritant Amount/concentration applied: 0.1 MI

Xylene, mixed isomers Rabbit - Eyes - Mild irritant

> Amount/concentration applied: 87 mg Rabbit - Eyes - Severe irritant

Duration of treatment/exposure: 24 hours Amount/concentration applied: 5 mg

Ethylbenzene Rabbit - Eyes - Severe irritant

Amount/concentration applied: 500 mg

**Conclusion/Summary [Product]** : Not available.

Respiratory corrosion/irritation

Not available.

**Conclusion/Summary [Product]** Not available.

Date of issue/Date of revision : 9/14/2025 Date of previous issue : 7/30/2025 Version: 30.04 15/24

8300 KRYLON® LINE-UP® Striping Paint (Solvent Based)

Highway White

#### Respiratory or skin sensitization

Not available.

Skin

**Conclusion/Summary [Product]** : Not available.

Respiratory

**Conclusion/Summary [Product]** : Not available.

Germ cell mutagenicity

Not available.

**Conclusion/Summary [Product]** : Not available.

**Carcinogenicity** 

Not available.

**Conclusion/Summary [Product]** : Not available.

#### Classification

Product/ingredient name	OSHA	IARC	NTP
Toluene	-	3	-
Titanium Dioxide	-	2B	-
Xylene, mixed isomers	-	3	-
Ethylbenzene	-	2B	-

#### Reproductive toxicity

Product/ingredient name

Not available.

8300

**Conclusion/Summary [Product]** : Not available.

#### Specific target organ toxicity (single exposure)

Result Acetone SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)

(Narcotic effects) - Category 3

Lt. Aliphatic Hydrocarbon Solvent SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)

(Narcotic effects) - Category 3

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) Toluene

(Narcotic effects) - Category 3

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) Xylene, mixed isomers

(Respiratory tract irritation) - Category 3

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)

SHW-85-NA-GHS-US

(Narcotic effects) - Category 3

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) Ethylbenzene

(Narcotic effects) - Category 3

#### Specific target organ toxicity (repeated exposure)

Product/ingredient name Result

Date of issue/Date of revision : 9/14/2025 Date of previous issue : 7/30/2025 Version: 30.04 16/24

KRYLON® LINE-UP® Striping Paint (Solvent Based)

Toluene SPECIFIC TARGET ORGAN TOXICITY (REPEATED

EXPOSURE) - Category 2

Xylene, mixed isomers SPECIFIC TARGET ORGAN TOXICITY (REPEATED

EXPOSURE) - Category 2

Ethylbenzene SPECIFIC TARGET ORGAN TOXICITY (REPEATED

EXPOSURE) - Category 2

**Aspiration hazard** 

Product/ingredient name Result

Lt. Aliphatic Hydrocarbon Solvent
Toluene
ASPIRATION HAZARD - Category 1
Ethylbenzene
ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure

Not available.

Potential acute health effects

**Eye contact** : Causes serious eye irritation.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or

dizziness.

Skin contact : Causes skin irritation.

**Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and

enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact**: Adverse symptoms may include the following:

pain or irritation watering redness

**Inhalation** : Adverse symptoms may include the following:

respiratory tract irritation

coughing

nausea or vomiting

headache

drowsiness/fatigue dizziness/vertigo unconsciousness reduced fetal weight increase in fetal deaths skeletal malformations

**Skin contact**: Adverse symptoms may include the following:

irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

**Ingestion** : Adverse symptoms may include the following:

nausea or vomiting reduced fetal weight increase in fetal deaths skeletal malformations

Date of issue/Date of revision : 9/14/2025 Date of previous issue : 7/30/2025 Version : 30.04 17/24

SHW-85-NA-GHS-US

8300 KRYLON® LINE-UP® Striping Paint (Solvent Based)

Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

Potential immediate

: Not available.

effects

Potential delayed effects

: Not available.

Long term exposure

**Potential immediate** 

: Not available.

effects

Potential delayed effects : No

: Not available.

Potential chronic health effects

Not available.

**Conclusion/Summary [Product]** : Not available.

General : May cause damage to organs through prolonged or repeated exposure.

Carcinogenicity: Suspected of causing cancer. Risk of cancer depends on duration and level of

exposure.

**Mutagenicity**: No known significant effects or critical hazards.

**Reproductive toxicity**: May damage fertility or the unborn child.

#### **Numerical measures of toxicity**

#### **Acute toxicity estimates**

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Acetone	5800	N/A	N/A	N/A	N/A
Butane	N/A	N/A	N/A	658	N/A
Toluene	N/A	N/A	N/A	49	N/A
Xylene, mixed isomers	4300	2500	N/A	N/A	N/A
Ethylbenzene	3500	N/A	N/A	11	N/A

## **Section 12. Ecological information**

#### **Toxicity**

Acetone

Product/ingredient name

- - - -

Result

Acute - EC50 - Fresh water

Algae - Green algae - Selenastrum sp.

7200 mg/l [96 hours] Effect: Population

Chronic - NOEC - Marine water Algae - Green algae - *Ulva pertusa* 

4.95 mg/l [96 hours] Effect: Reproduction

**Chronic - NOEC - Fresh water** Crustaceans - Daphnia - *Daphniidae* 

0.016 ml/l [21 days] Effect: Population

**Chronic - NOEC - Marine water** 

Fish - Threespine stickleback - Gasterosteus aculeatus - Larvae

Date of issue/Date of revision : 9/14/2025 Date of previous issue : 7/30/2025 Version : 30.04 18/24

8300 KRYLON® LINE-UP® Striping Paint (Solvent Based)

Highway White

Age: 7 days 5 µg/l [42 days] Effect: Population

Acute - LC50 - Marine water

Crustaceans - Calanoid copepod - Acartia tonsa - Copepodid

4.42589 ml/l [48 hours]

Effect: Mortality

Acute - LC50 - Fresh water Fish - Guppy - Poecilia reticulata

Age: 4 to 12 months; Size: 2 to 10 cm; Weight: 0.5 to 14 g

5600 ppm [96 hours] Effect: Mortality

Lt. Aliphatic Hydrocarbon Solvent

Acute - LC50 - Fresh water

**US EPA** 

Fish - Rainbow trout, donaldson trout - Oncorhynchus mykiss

Weight: 0.32 g >10 pph [96 hours] Effect: Mortality

Toluene Acute - LC50 - Fresh water

Fish - Coho salmon, silver salmon - Oncorhynchus kisutch - Fry

Weight: 1 g

5500 µg/l [96 hours] Effect: Mortality

Acute - EC50 - Fresh water

Daphnia - Water flea - Daphnia magna - Juvenile (Fledgling,

Hatchling, Weanling) 6000 µg/l [48 hours] Effect: Intoxication

Chronic - NOEC - Fresh water

Daphnia - Water flea - Daphnia magna

Age: ≤24 hours 1 mg/l [21 days] Effect: Mortality

Acute - EC50 - Fresh water

Algae - Green algae - Raphidocelis subcapitata

12.5 mg/l [72 hours] Effect: Growth

Titanium Dioxide Acute - LC50 - Marine water

Fish - Mummichog - Fundulus heteroclitus

>1000 mg/l [96 hours]

Effect: Mortality

Xylene, mixed isomers Acute - LC50 - Marine water

Crustaceans - Daggerblade grass shrimp - Palaemon pugio

8500 µg/l [48 hours] Effect: Mortality

Acute - LC50 - Fresh water

Fish - Fathead minnow - Pimephales promelas Age: 31 days; Size: 18.4 mm; Weight: 0.077 g

13.4 mg/l [96 hours] Effect: Mortality

Light Aliphatic Hydrocarbon Acute - LC50 - Fresh water

Fish - Bluegill - Lepomis macrochirus

Size: 35 to 75 mm 2200 µg/l [4 days] Effect: Mortality

Acute - LC50 - Fresh water

8300

Ethylbenzene

Date of issue/Date of revision : 9/14/2025 Date of previous issue : 7/30/2025 Version: 30.04 19/24

KRYLON® LINE-UP® Striping Paint (Solvent Based)

Fish - Rainbow trout, donaldson trout - Oncorhynchus mykiss

4200 µg/l [96 hours] Effect: Mortality

Acute - EC50 - Fresh water

Daphnia - Water flea - Daphnia magna - Neonate

Age: ≤24 hours 2.93 mg/l [48 hours] Effect: Intoxication

Acute - EC50 - Fresh water

Algae - Green algae - Raphidocelis subcapitata

3600 µg/l [96 hours] Effect: Population

**Conclusion/Summary [Product]** : Not available.

#### Persistence and degradability

Not available.

**Conclusion/Summary [Product]** : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Acetone	-	-	Readily
Toluene	-	-	Readily
Xylene, mixed isomers	-	-	Readily
Ethylbenzene	-	-	Readily

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Lt. Aliphatic Hydrocarbon Solvent	-	10 to 2500	High
Toluene Xylene, mixed isomers	-	90 8.1 to 25.9	Low Low

#### **Mobility in soil**

Soil/Water partition coefficient

: Not available.

#### Other adverse effects

No known significant effects or critical hazards.

### Section 13. Disposal considerations

#### **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

Date of issue/Date of revision : 9/14/2025 Date of previous issue : 7/30/2025 Version: 30.04 20/24 8300

## **Section 14. Transport information**

	DOT Classification	TDG Classification	Mexico Classification	IATA	IMDG
UN number	UN1950	UN1950	UN1950	UN1950	UN1950
UN proper shipping name	AEROSOLS	AEROSOLS	AEROSOLS	AEROSOLS, flammable	AEROSOLS
Transport hazard class(es)	2.1	2.1	2.1	2.1	2.1
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	-	Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.13-2.17 (Class 2).		_	Emergency schedules F-D, S- U
	ERG No.	ERG No.	ERG No.		
	126 Dependent upon container size, this product may ship under the Limited Quantity shipping exception.	126 Dependent upon container size, this product may ship under the Limited Quantity shipping exception.	Dependent upon container size, this product may ship under the Limited Quantity shipping exception.	Dependent upon container size, this product may ship under the Limited Quantity shipping exception.	Dependent upon container size, this product may ship under the Limited Quantity shipping exception.

Special precautions for user :

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according: Not available. to IMO instruments

**Proper shipping name** : Not available.

## Section 15. Regulatory information

**U.S. Federal regulations SARA 313** 

Date of issue/Date of revision : 9/14/2025 Date of previous issue : 7/30/2025 Version: 30.04 21/24

## Section 15. Regulatory information

All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED and rely on information provided to us by our raw material suppliers. Our suppliers often provide an estimated value or range less than a certain upper limit. We calculate MAXIMUM THEORETICAL VALUES using defined values, if provided, or the upper limit reported by our supplier. Additionally, the suppliers' information may include amounts present in the product as unintentional byproducts or impurities. Variations may occur in individual batches due to adjustments made during production. Reporting of chemicals in this section does not necessarily indicate their presence in the final formulated product.

Ingredient name	% by weight	CAS number
Mercury (as Hg)	0.000002	
Toluene	8	108-88-3
Ethylbenzene	0.1	100-41-4
Lead (as Pb)	0.00006	

#### California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

#### International regulations

#### **Montreal Protocol**

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

International lists

: Australia inventory (AIIC): Not determined. China inventory (IECSC): Not determined. Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined. Korea inventory (KECI): Not determined.

New Zealand Inventory of Chemicals (NZIoC): Not determined.

Philippines inventory (PICCS): Not determined.

Taiwan Chemical Substances Inventory (TCSI): Not determined.

Thailand inventory: Not determined. Turkey inventory: Not determined. Vietnam inventory: Not determined.

### Section 16. Other information

#### **Hazardous Material Information System (U.S.A.)**



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

Date of issue/Date of revision : 9/14/2025 Date of previous issue : 7/30/2025 Version : 30.04 22/24
8300 KRYLON® LINE-UP® Striping Paint (Solvent Based)
Highway White : 9/14/2025 Date of previous issue : 7/30/2025 Version : 30.04 22/24
SHW-85-NA-GHS-US

### Section 16. Other information

Classification	Justification
AEROSOLS - Category 1	On basis of test data
SKIN CORROSION/IRRITATION - Category 2	Calculation method
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A	Calculation method
CARCINOGENICITY - Category 2	Calculation method
TOXIC TO REPRODUCTION - Category 1B	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) -	Calculation method
Category 3	
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2	Calculation method
ASPIRATION HAZARD - Category 1	Calculation method

#### **History**

Date of printing 9/14/2025 9/14/2025 Date of issue/Date of

revision

Date of previous issue 7/30/2025 **Version** 30.04

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available SGG = Segregation Group UN = United Nations

Indicates information that has changed from previously issued version.

#### Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buver/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

Date of issue/Date of revision : 9/14/2025 Date of previous issue : 7/30/2025 Version: 30.04 23/24

8300