

# Safety Data Sheet

24 Hour Emergency Phone Numbers Medical/Poison Control:

In U.S.: Call 1-800-222-1222

Outside U.S.: Call your local poison control center

Transportation/National Response Center:

1-800-535-5053 1-352-323-3500

NOTE: The National ResponseCenter emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

IMPORTANT: Provide this information to employees, customers, and users of this product. Read this SDS before handling or disposing of this product. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard. All abbreviated terms used in this MSDS are further described in Section 16.

### 1. Identification

This Material Safety Data Sheet is available in American Spanish upon request. Los Datos de Serguridad del Producto pueden obtenerse en Espanol si lo riquiere.

Product Name: Daptex Plus Multi-Purpose Foam Sealant Revision Date: 6/19/2015

Product UPC Number: 18836 Supercedes Date: 12/27/2011

Product Use/Class: Foam Sealant SDS No: 00077344001

Manufacturer: DAP Products Inc.

2400 Boston Street Suite 200 Baltimore, MD 21224-4723

888-327-8477 (non - emergency matters)

Preparer: Regulatory Department

#### 2. Hazards Identification

**EMERGENCY OVERVIEW:** Under normal use conditions, this product is not expected to cause adverse health effects. Contents under pressure. Do not puncture can. Exposure to temperatures above 120 'F may cause can to rupture. This product contains ethylene glycol.

### **GHS Classification**

Comp. Gas, Eye Irrit. 2, Fl Aer, 1, Flam. Gas 1

### Symbol(s) of Product



Signal Word

Danger

#### **GHS HAZARD STATEMENTS**

Flammable Gas, category 1 H220 Extremely flammable gas.

Flammable Aerosol, category 1 H222 Extremely flammable aerosol.

Compressed Gas H280 Contains gas under pressure; may explode if heated.

Eye Irritation, category 2 H319 Causes serious eye irritation.

#### **GHS LABEL PRECAUTIONARY STATEMENTS**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P377 If eye irritation persists:

P381 Eliminate all ignition sources if safe to do so.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do no expose to temperatures exceeding 50°C/ 122°F.

# 3. Composition/Information on Ingredients

Chemical Name	CAS-No.	Wt. % GHS Symbols	<b>GHS Statements</b>
Isopropyl alcohol	67-63-0	2.5-10 GHS02-GHS03-	H225-270-319-332-336
		GHS07	
Ethylene glycol	107-21-1	1.0-2.5 GHS03-GHS06	H270-331
1-Docosanol	661-19-8	1.0-2.5 GHS03	H270
Dimethyl ether	115-10-6	1.0-2.5 GHS03	H270
Propane	74-98-6	1.0-2.5 GHS03-GHS07	H270-332-336
n-Butane	106-97-8	1.0-2.5 GHS03-GHS07	H270-332-336
Alcohol C11-14-ISO C13 Rich Ethoxylated	78330-21-9	1.0-2.5 GHS03-GHS05	H270-315-318

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

# 4. First-aid Measures

**FIRST AID - INHALATION:** Material is not likely to present an inhalation hazard at ambient conditions. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

**FIRST AID - SKIN CONTACT:** No health hazards are known to exist. Use a rag to remove excess foam from skin and remove contaminated clothing. Use of a solvent, such as acetone (nail polish remover) or mineral spirits, may help in removing uncured foam residue from clothing or other surfaces (avoid eye contact). Cured foam may be physically removed by persistent washing with soap and water. If irritation develops, use mild skin cream. If irritation persists, obtain medical attention. In case of contact, wash skin immediately with soap and water.

**FIRST AID - EYE CONTACT:** In case of contact, immediately flush eyes with large quantities of water for at least 15 minutes until irritation subsides. Get medical attention immediately.

FIRST AID - INGESTION: If swallowed, DO NOT INDUCE VOMITING. Get medical attention immediately.

### 5. Fire-fighting Measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers may burst if exposed to extreme heat or fire. None known.

**SPECIAL FIREFIGHTING PROCEDURES:** Wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear. Use water spray to cool exposed surfaces.

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam, Water Fog

#### 6. Accidental Release Measures

**ENVIRONMENTAL MEASURES:** No Information

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: NOTE: Review fire hazards before proceeding with clean up. Immediately eliminate sources of ignition. Keep people away from and upwind of spill/leak. Contain spilled material and remove with

inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Scrape up dried material and place into containers. Prevent product from entering drains. Soak up with inert absorbent material and dispose of as hazardous waste. Use personal protective equipment as necessary. Read all product instructions before using. Personal protective equipment should include impervious gloves, protective eye wear, and suitable work clothes. Uncured product is very sticky, so carefully remove the bulk of the foam by scraping it up and then immediately remove residue with a rag and solvent such as polyurethane cleaner, mineral spirits, acetone (nail polish remover), paint thinner, etc. Once the product has cured, it can only be removed physically by scraping, buffing, etc. Dispose as plastic waste (foam plastic) in accordance with all applicable guidelines and regulations.

# 7. Handling and Storage

**HANDLING:** KEEP OUT OF REACH OF CHILDREN!DO NOT TAKE INTERNALLY. Make sure nozzle is directed away from yourself prior to discharge. Keep away from open flames, hot surfaces and sources of ignition. Use only with adequate ventilation. Ensure fresh air entry during application and drying. Wash thoroughly after handling.

**STORAGE:** Protect material from direct sunlight. Keep containers tightly closed in a dry, cool and well-ventilated place. Do not store at temperatures above 120 degrees F. Store containers away from excessive heat and freezing. Store away from caustics and oxidizers.

# 8. Exposure Controls/Personal Protection

Ingradianta	with	Occupational	Evenouse	Limita
Inarealents	with	Occupational	Exposure	Limits

Chemical Name	ACGIH TLV-TWA	ACGIH-TLV STEL	OSHA PEL-TWA	OSHA PEL-CEILING
Isopropyl alcohol	200 ppm TWA	400 ppm STEL	400 ppm TWA, 980 mg/m3 TWA	N.E.
Ethylene glycol	N.E.	N.E.	N.E.	N.E.
1-Docosanol	N.E.	N.E.	N.E.	N.E.
Dimethyl ether	N.E.	N.E.	N.E.	N.E.
Propane	1000 ppm TWA Aliphatic hydrocarbon gases: Alkane C1-4	N.E.	1000 ppm TWA, 1800 mg/m3 TWA	N.E.
n-Butane	N.E.	1000 ppm STEL	N.E.	N.E.
Alcohol C11-14-ISO C13 Rich Ethoxylate	d N.E.	N.E.	N.E.	N.E.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

#### Personal Protection



**RESPIRATORY PROTECTION:** No personal respiratory protective equipment normally required.



**SKIN PROTECTION:** Rubber gloves.



**EYE PROTECTION:** Goggles or safety glasses with side shields.



OTHER PROTECTIVE EQUIPMENT: Not required under normal use.



**HYGIENIC PRACTICES:** Wash hands before breaks and at the end of workday. Remove and wash contaminated clothing before re-use.

Physical State:

Odor Threshold:

Viscosity (mPa.s):

Explosive Limits, %:

Flash Method:

Vapor Pressure, mmHg:

Partition Coeff., n-octanol/water:

Auto-Ignition Temperature, °C

pH:

Foam

Not Established

Not Established

Not Established

Not Established

No Information

Not Applicable

N.I. - N.I.

Between 7.0 and 12.0

# 9. Physical and Chemical Properties

Appearance: White Odor: Slight Alcoholic 0.99 - 0.99Density, g/cm3: Freeze Point, °C: Not Established Solubility in Water: Not Established Decomposition Temperature, °C: Not Established Boiling Range, °C: N.I. - N.I.

Minimum Flash Point, °C: No Information **Evaporation Rate:** Slower Than n-Butyl Acetate

Vapor Density: Heavier Than Air

Combustibility: Does not support combustion

(See "Other information" Section for abbreviation legend)

(If product is an aerosol, the flash point stated above is that of the propellant.)

# 10. Stability and Reactivity

**STABILITY:** Stable under recommended storage conditions.

CONDITIONS TO AVOID: Excessive heat and freezing.

**INCOMPATIBILITY:** Incompatible with strong bases and oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Normal decomposition products, i.e., COx, NOx.

# 11. Toxicological Information

EFFECT OF OVEREXPOSURE - INHALATION: Under normal use conditions, this product is not expected to cause adverse health effects. Inhalation of vapors in high concentration may cause mild irritation of respiratory system (nose, mouth, mucous membranes).

EFFECT OF OVEREXPOSURE - SKIN CONTACT: Under normal use conditions, this product is not expected to cause adverse health effects. Prolonged or repeated contact with skin may cause mild irritation.

EFFECT OF OVEREXPOSURE - EYE CONTACT: Under normal use conditions, this product is not expected to cause adverse health effects. Direct eye contact may cause irritation. Mist and vapors may cause eye irritation. Foam contact can cause physical damage due to adhesive character.

EFFECT OF OVEREXPOSURE - INGESTION: Under normal use conditions, this product is not expected to cause adverse health effects. Single dose oral toxicity is very low. Amounts ingested incidental to industrial handling are not likely to cause injury; however, ingestion of large amounts may cause injury. Ingestion of ethylene glycol can cause gastrointestinal irritation, nausea, vomiting, diarrhea and if ingested in sufficient quantities, death.

**CARCINOGENICITY:** No Information

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Inhalation, Skin Absorption, Skin Contact

### **Acute Toxicity Values**

The acute effects of this product have not been tested. Data on individual components are tabulated below

<u>CAS-No.</u> 67-63-0	Chemical Name Isopropyl alcohol	Oral LD50 4396 mg/kg Rat	Dermal LD50 12800 mg/kg Rabbit	Vapor LC50 N.I.
107-21-1	Ethylene glycol	4000 mg/kg Rat	9530 mg/kg Rabbit	> 2.5 mg/L Rat
661-19-8	1-Docosanol	>10000 mg/kg Rat	258015 mg/kg Rabbit	N.I.
115-10-6	Dimethyl ether	>2000 mg/kg	>2000 mg/kg	308.5 mg/L Rat
74-98-6	Propane	Not an exposure route	N.I.	658 mg/L Rat

106-97-8 n-Butane Not an exposure route N.I. 658 mg/L Rat

78330-21-9 Alcohol C11-14-ISO C13 Rich Ethoxylated N.I. N.I. N.I. N.I.

N.I. = No Information

# 12. Ecological Information

ECOLOGICAL INFORMATION: Ecological injuries are not known or expected under normal use.

# 13. Disposal Information

DISPOSAL INFORMATION: Residues and spilled material are hazardous waste due to ignitability. Contents under pressure. Dispose of material in accordance with all federal, state and local regulations. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste. Do not flush into surface water or sanitary sewer system. Do not empty into drains. Do not re-use empty containers. The container for this product can present explosion or fire hazards, even when emptied. To avoid risk of injury, do not cut, puncture, or weld on or near this container. Before disposing of containers, relieve container of any remaining product and pressure. Empty cylinders, once relieved of all pressure, can be disposed of as non-hazardous waste.

# 14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No Information

DOT UN/NA Number: UN1950

**DOT Proper Shipping Name:** Aerosols, flammable

DOT Technical Name: N.A.

DOT Hazard Class: 2.1

Hazard SubClass: N.A.

Packing Group: N.A.

### 15. Regulatory Information

### U.S. Federal Regulations:

#### **CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Pressure Hazard, Acute Health Hazard, Chronic Health Hazard

### **SARA SECTION 313:**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical NameCAS-No.Ethylene glycol107-21-1

#### TOXIC SUBSTANCES CONTROL ACT:

All ingredients in this product are either on TSCA inventory list, or otherwise exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

#### **CALIFORNIA PROPOSITION 65 CARCINOGENS**

This product does not contain any chemicals known to the State of California to cause cancer.

### **CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS**

This product does not contain any chemicals known to the State of California to cause birth defects or other reproductive harm.

### International Regulations: As follows -

#### **CANADIAN WHMIS:**

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

WHMIS Class Consumer Commodity

# 16. Other Information

Revision Date: 6/19/2015 Supersedes Date: 12/27/2011

Reason for revision: HazCom2012/GHS Conversion

Datasheet produced by: Regulatory Department

**HMIS Ratings:** 

Health:	1	Flammability:	3	Reactivity:	0	Personal Protection:	Х

VOC Less Water Less Exempt Solvent, g/L<sub>163.7</sub>

VOC Material, g/L:108

VOC as Defined by California Consumer Product Regulation, Wt/Wt%:8.5

### Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H225	Highly flammable liquid and vapour.
H270	May cause or intensify fire; oxidiser.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.

#### Icons for GHS Pictograms shown in Section 3 describing each ingredient:



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

DAP believes the data and statements contained herein are accurate as of the date hereof. They are offered in good faith as typical values and not as a product specification. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE WITH REGARD TO THE INFORMATION HEREIN PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS. Since this document is intended only as a guide to the appropriate use and precautionary handling of the referenced product by a properly trained person, it is therefore the responsibility of the user to (i) review the recommendations with due consideration for the specific context of the intended use and (ii) determine if they are appropriate.